

Hillside Works

**Guidelines to the Restoration
of Vegetation on Wasteland**

Table of Contents

| | |
|--|-----------|
| 1. Before execution hillside works | 1 |
| 1.1 What are hillside works?..... | 1 |
| 1.2 To avoid failure..... | 2 |
| 2. Improvement targets | 4 |
| 2.1 What degree of improvement is considered as a sabo project..... | 4 |
| 2.2 To the formation of the target forest..... | 4 |
| 3. Selecting an effective method | 7 |
| 3.1 To restore greenery on hillside slopes | 7 |
| 3.2 To encourage the transition to the target forest..... | 10 |
| 4. Evaluation and appropriate management of the degree of achievement of the improvement target | 14 |
| 4.1 Why is an evaluation necessary?..... | 14 |
| 4.2 What is the object of the evaluation?..... | 14 |
| 4.3 What is appropriate management? | 15 |
| 5. Cases of hillside work in Japan | 17 |
| Case 1 Matsuki Hillside Work..... | 17 |
| Case 2 Ohya Hillside Work | 18 |
| Case 3 Tanakami Hillside Work..... | 19 |
| Case 4 Tsuchiyabara Hillside Work..... | 20 |
| Case 5 Rokkozan Chain Green Belt..... | 21 |
| Case 6 Dashidaira Revegetation Work | 22 |
| Case 7 Ushibuse River Forest Physiognomy Transformation | 23 |
| Appendix | |
| Hillside Works(Manual for River Works in Japan) | 24 |